

WATER PUMPS



T SERIES PRO



Model no.	Performance	Height Max (ft)	Power consumption (w)	Outlet Size (")	Dimensions (") (LxWxH)
	Max Flow (Gallons/hour)				
T4000	1057	8.5	58	1, 1 ¹ / ₄ , 1 ¹ / ₂	14.1x5.2x6.4
T5000	1295	9.7	64	1, 1 ¹ / ₄ , 1 ¹ / ₂	14.1x5.3x6.4
T6000	1453	9.8	75	1, 1 ¹ / ₄ , 1 ¹ / ₂	14.1x5.3x6.4
T8000	2061	11.8	91	1, 1 ¹ / ₄ , 1 ¹ / ₂	14.1x5.3x6.4
T9000	2357	13.1	105	1, 1 ¹ / ₄ , 1 ¹ / ₂	14.1x5.3x6.4
T10000	2510	13.1	125	1, 1 ¹ / ₄ , 1 ¹ / ₂	14.1x5.3x6.4
T12000	3118	14.1	145	1, 1 ¹ / ₄ , 1 ¹ / ₂	14.1x5.3x6.4
T15000	3857	18.0	220	1 ¹ / ₂ , 2	15.8x6.5x7.4
T18000	4518	19.7	285	1 ¹ / ₂ , 2	15.8x6.5x7.4
T20000	4835	21.9	320	1 ¹ / ₂ , 2	15.8x6.5x7.4
T23000	5548	27.8	500	1 ¹ / ₂ , 2	15.8x6.5x7.4
T25000	6341	31.1	580	1 ¹ / ₂ , 2	15.8x6.5x7.4

AVAILABLE WITH
10M CABLE

- ✓ Can be used submersed or inline.
- ✓ Synchronous motor with overload protection by means of a thermal overload trip.
- ✓ Spare parts & rotor housing available.
- ✓ Exceptionally high flow.
- ✓ Vortex impeller.

