

# Quest 132D

Desiccant Dehumidifier

1.877.420.1330  
www.QuestHydro.com



<b>Specifications:</b>		
<b>Part Number:</b>	4037900	
<b>Power:</b>	63 KWh/Day	
<b>Supply Voltage:</b>	2 Circuits; 11Amps, 115VAC each 22 Amps total power consumption	
<b>Capacity:</b>	132 Pints (80°F 60%RH)	
<b>Process Air:</b>	385 CFM Process Airflow @ 0" ESP 75 CFM Reactivation Airflow @ 0"ESP	
<b>Operating Range:</b>	10°F to 120°F	
<b>Filters:</b>	Process Filter Size: 16" X 20" X 2" Reactivation Filter Size: 12" X 12" X 1"	
<b>Duct Options:</b>	Reactivation Duct: 6" (Start collars included) Connections Process Duct: 8" (Start collars included)	
<b>Warranty:</b>	1 year 100% parts and labor	
<b>Dimensions:</b>		
	Unit	Shipping
<b>Width:</b>	20"	25"
<b>Height:</b>	36"	47"
<b>Depth:</b>	20"	24"
<b>Weight:</b>	105 lbs	125 lbs

### Water Removal Rates (Pints/Day)

65 Pints	100°F, 20%
180 Pints	90° F, 90%
150 Pints	80° F, 80%
<b>132 Pints</b>	<b>80° F, 60% (AHAM)</b>
130 Pints	70° F, 80%
120 Pints	70° F, 60%
115 Pints	60° F, 80%
125 Pints	60° F, 60%
110 Pints	50° F, 80%
100 Pints	50° F, 60%
30 Pints	10° F, 80%

