

# COVERT UFO

## MAX AMPERAGE BY VOLTAGE

| VOLTAGE | 100V  | 208V  | 240V  |
|---------|-------|-------|-------|
| 150W    | 1.50A | 0.72A | 0.63A |




|                        |   |
|------------------------|---|
| Input Power            | 150W  |
| Efficacy               | 2.1 μmol/s  |
| PPF                    | 315 μmol/s  |
| Input Voltage          | Autosensing 100-240V                                  |
| Mounting Height        | ≥12"(30cm) Above Canopy                               |
| Thermal Management     | Passive   |
| Lifetime               | 50,000hrs   |
| Power Factor           | >90%  |
| Certifications         | UI1598 Damp Location Rating & IP55 (Console Only), CE |
| Colour Rendering Index | 90ra  |
| Ambient Temperture     | -4~104F   |
| Operating Temp Range   | -4~185F RH10%-95%                                     |
| Chip                   | BRANDED LED   |
| Fixture Dimensions     | 14" H6"<br>(360*H150MM)                               |
| Fixture Weight         | 6.3Lb/2.9kg   |

## FULL SPECTRUM

Real Full Spectrum (Sunlight) For Plant From Veg Growth TO Bloom. No Need to Change Anything in Whole Growing.



- Array LEDs provide uniform light spread
- Fixture built with high-quality LED Drivers for optimum performance




## SILENT OPERATION



High-End & High-Performance  
Self-Heating Dissipation Feature.  
Loud Fan No Need



Traditional Loud Fan



Other's

## PLUG & PLAY



Very convenient and hassle free installation.

- plug & play
- Solid Suspension system  
1/8 inch adjustable heavy rope hanger

## DURABLE HOUSING



Durable aluminum structure is waterproof which ensures long lifespan

## HEAT MANAGEMENT



Die-casting aluminum with excellent heat dissipation

## LOW ENERGY USE



Energy-efficient LED technology lowers energy usage.