

EZ-Breeze HAF Basket Fan

J&D Manufacturing's EZ-Breeze HAF Fan is a high-efficiency air circulator that effectively cools people, plants, animals and industrial equipment. The EZ-Breeze reduces condensation, dries animal litter and bedding, controls insects, and creates a uniform temperature throughout your building to reduce heating costs.

Features

- Available in 12", 16", 20" and 24"
- Includes hot dip galvanized mounting bracket with u-bolts and nuts
- Aluminum propeller designed to reduce ambient noise levels while maintaining maximum circulation requirements
- Efficient variable speed motors (*requires separate variable speed control to adjust fan speed*)
- Corrosion resistant, white powder coated fan guards meet OSHA 1910.212(a)(5) requirements
- Fan ships completely assembled
- Attached 10' cord with 3-prong plug pre-wired for 115 volts
- Totally enclosed, maintenance-free, direct drive high-efficiency motors have completely sealed ball bearings, are UL/CUL recognized, and are covered by a **Two Year Warranty**
- For additional cooling, use with our misting/fogging product line



Guards Meet OSHA Requirements

Part#	Size	HP	Volts	Amps ^{NP}	Hz [~]	Ph	Spd	FPM	Thrust (lbf)	Thrust Eff. Ratio	kW	RPM	Thrust CFM	Thrust CFM/Watt	Cord	Blade	Included Bracket	Test #
VDB12G	12"	1/10	115 [~]	1.0	60	1	1/Var [^]	565	0.84	7.2	.117	1,695	1,030	8.8	10'	3-Alm	VRSBR736-U	C09006
VDB16G	16"	1/10	115	1.0	60	1	1/Var [^]	805	1.17	11.7	.100	1,719	1,620	16.2	10'	3-Alm	VRSBR736-U	C09007
VDB20G	20"	1/10	115 [~]	1.0	60	1	1/Var [^]	575	0.80	7.9	.102	1,715	1,680	16.5	10'	3-Alm	VRSBR8-U	C09008
VDB203G	20"	1/3	115	3.5	60	1	1/Var [^]	870	3.19	8.7	.367	1,685	3,340	9.1	10'	3-Alm	VRSBR8-U	N/A
VDB24G	24"	1/3	115 [~]	3.5	60	1	1/Var [^]	940	3.09	8.0	.384	1,680	3,920	10.2	10'	3-Alm	VRSBR5-U	N/A
VDB242G	24"	1/2	115	4.8	60	1	1/Var [^]	1,150	5.79	11.6	.498	1,709	5,370	10.8	10'	3-Alm	VRSBR5-U	N/A

All EZ-Breeze HAF fans are direct drive, have white guards, and include standard bracket hardware.

All units are Direct Drive and include the corresponding hot dip galvanized standard flag mount bracket with hardware.

^{NP} Amp information as documented on motor name plate

[~] These units come pre-wired for 115 Volts (electrician may rewire for 230 Volts)

[^] For 50 Hz compatibility data please contact J&D Manufacturing

[^] Variable speed fans require separate variable speed control to adjust fan speed.

N/A Test number "not available"

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12.



Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.