



MANUAL DISC FILTERS

RELIABLE, EFFICIENT PLASTIC DISCS CREATE SUPERIOR FILTRATION



PRODUCT ADVANTAGES

- Highly effective multiple disc ring design captures and holds more debris.
- Greater holding capacity of the rings vs. screen filters mean less frequent cleaning.
- Rings are easily removed for fast cleaning without the need for scrubbing.

APPLICATIONS

- Primary irrigation filter for relatively clean or average water quality
- Protection of irrigation systems from clogging and/or abrasion




THE FILTERING PROCESS


Grooved, compressed plastic disc rings produce a deep filtration process. As dirty water is pumped into the filter and pressure increases on the outside of the filter, the water pressure compresses the rings together tightly.

Grooves in the disc rings crisscross, forming a three dimensional network that traps particles. The number of crisscrossed intersection points on each groove varies, depending on filtration grade. The turbulence in the varying paths and the large number of intersections create an environment where particles are eventually trapped.

This design filters the dirty water thoroughly, not only on the outer surface of the cylindrical disc filter, but through the entire depth of every ring's grooves. The result is a larger, more efficient filtering area (when compared to screen filters) with more debris being captured and cleaner water exiting from the filter.



Top view of disc ring



MANUAL DISC FILTERS



3/4" FILTER		
FLOW RANGE	1 - 12 GPM	
MAXIMUM PRESSURE	140 psi	
FILTERING SURFACE AREA	25 sq. in.	
FILTERING VOLUME	5.8 cu. in.	
LENGTH	5 22/32"	
WIDTH	7 15/32"	
WEIGHT	.66 lbs.	
DISTANCE BETWEEN ENDS	6"	
INLET/OUTLET DIAMETER	3/4" Male	
NETAFIM MODEL NUMBER	25A45-140	
HAWTHORNE MODEL NUMBER	HGC747733	



1" FILTER	
FLOW RANGE	5 - 26 GPM
MAXIMUM PRESSURE	140 psi
FILTERING SURFACE AREA	49 sq. in.
FILTERING VOLUME	27 cu. in.
LENGTH	9 11/32"
WIDTH	6 7/32"
WEIGHT	2.2 lbs.
DISTANCE BETWEEN ENDS	6 7/32"
INLET/OUTLET DIAMETER	1" Male
NETAFIM MODEL NUMBER	25A47-140
HAWTHORNE MODEL NUMBER	HGC47734



1 ½" SUPER FILTER		
FLOW RANGE	10 - 52 GPM	
MAXIMUM PRESSURE	140 psi	
FILTERING SURFACE AREA	78 sq. in.	
FILTERING VOLUME	36 cu. in.	
LENGTH	14 1/2"	
WIDTH	7 7/8"	
WEIGHT	3.3 lbs.	
DISTANCE BETWEEN ENDS	7 7/8"	
INLET/OUTLET DIAMETER	1 1/2" Male	
NETAFIM MODEL NUMBER	25A17-140	
HAWTHORNE MODEL NUMBER	HGC747756	

MATERIALS

Disc Rings: PolypropyleneO-Rings: EPDM RubberClamp: Stainless Steel

FILTER APPLICATION RECOMMENDATIONS

FLOW RATE	HEADLOSS (psi)		
(GPM)	3/4"	1″	1 1/2" SUPER
5	0.60	0.25	
10	2.50	0.60	
13	3.40	1.34	
17	5.87	2.10	
22		3.24	
26			1.50
31			2.10
35			2.50
44			4.20

The losses shown are for filters with 140 Mesh

CHART LEGEND

CHAIT LEGEND				
0.00	River, ditch, pond, lake or reservoir water			
0.00	Well water containing sand only			
0.00	Municipal supply			

