



Under Canopy Lighting 8Ft



GPS-UCL-250 W

Upgrade your cultivation and leave no buds behind. By utilizing our specially designed under canopy lights you can maximize your growth and yields by illuminating the previously underlit areas of your plants.

FFATURES & BENEFITS

- Improve B-bud size, structure, density, and coloring.
- Optimized full spectrum proven by growers great for veg and exceptional for boosting flower - includes 3000k, 5000k, 660nm Deep Red, and 730nm infrared diodes.
- IP65 rated for easy cleaning and protection from IPM sprays, irrigation leaks, and employees getting crazy with the watering wand.
- Compact and lightweight, quick to set up, easy to work around for harvest or quick to uninstall when between trellis layers.
- One Under Canopy Light will cover 8' in length and 3' in width of under canopy, add a second row to further increase your yields!



Hang from above in static canopies or use our height adjustable legs with rolling benches.

LINK UP MULTIPLE FIXTURES
Power Chaining and Data Chaining through same connections, no extra wires required.

Daisy chain option:

- 4 pcs @ 120V 5 pcs @ 208V 6 pcs @ 240V 8 pcs @ 277V

ADJUSTABLE HEIGHT -----

Telescopic legs adjust to the plant growth for the perfect light coverage. *Leas sold seperately

REPLACABLE LENS

Lens is easy to replace and exchange with new lens after a few runs.

> Aluminum housing results in 10x faster heat dissipation compared to plastic shells.

> > *Legs Sold Seperately

Rated IP65: worrv free when spraying



Address: 4833 Lanier Road, Chino, CA 91710


Tel: (800) 383-6200 | **Email:** info@wegrowpros.com



LED LIGHTING SOLUTION FOR COMMERCIAL, INDOOR, AND GREENHOUSE APPLICATIONS

SPECIFICATIONS	
WATTAGE	250W
INPUT VOLTAGE	120V-277V
CONTROL	0-10V DIMMING
DATA CONNECTION	RJ-12
POWER FACTOR	>0.9
THERMAL MANAGEMENT	PASSIVE
WORKING TEMPERATURE	0°F to 104°F
IP RATING	Waterproof IP65
LIFETIME	L90: >36,000 hrs
WARRANTY	5 YEARS
CERTIFICATIONS	ETL, FCC
HEAT LOAD PER FIXTURE	852.5 BTUs

PERFORMANCE DATA	MAX POWER
PPE	2.6 μmol/s
PPF	650 μmol/s



MAXIMUM POWER ELECTRICAL DATA

	120V	208V	240V	277V
AC CURRENT	2.08A	1.20A	1.04A	0.90A
AC POWER	131.5W	126.9W	126.4W	126.1W
POWER FACTOR	0.99	0.99	0.98	0.97
DAISY CHAIN	4	5	6	8


WHAT'S IN THE BOX - RETAIL PACKAGE

4x 8ft Under Canopy Lights 1x 240V Plug Power Cord with attached RJ12 Data Cable 1x End Cap

1x 16ft RJ12 Data Cable 1x RJ12 Y-Splitter

BOX GROSS WEIGHT: 38 lbs

DIMENSIONS



Address: 4833 Lanier Road, Chino, CA 91710

Tel: (800) 383-6200 | **Email:** info@wegrowpros.com