

# OVERHEAD DEHUMIDIFIER BT-530



## BENEFITS OF THE BIOTHERM DEHUMIDIFIERS

- ENHANCED DEHUMIDIFICATION COMPARED TO INDUSTRY COMPETITORS
- EASILY SERVICEABLE
- EASILY INTEGRATED INTO PRE-EXISTING CONTROLS

The BT-530 Dehumidifier has been meticulously designed with today's indoor grow environmental challenges squarely as its foundation.

Independent laboratory testing has proved the BT-530 airflow rate is superior to its closets rivals in tests performed at the industry standard conditions of 80°F/ 60%RH. This industry leading performance results in potentially requiring less units to cover a grow area than comparable units.

At 530PPD the BT-530 is the perfect size not only to compliment an existing system but to be utilized as the main unit in smaller grows.

## SPECIFICATIONS

<b>Dehumidifying Capacity (80°F/60%RH)</b>	530 PPD
<b>Air Volume</b>	1,884 CFM
<b>Coverage Area</b>	3,770 FT.
<b>Operating Temp.</b>	41-110°F
<b>Operating Humidity</b>	20-95 RH
<b>Voltage Input</b>	208-240/1/60
<b>Power Input</b>	2900 W
<b>Running Current</b>	13.3 (208-240V)
<b>Refrigerant R410A Charge</b>	106 OZ.
<b>Sound Level</b>	75 dB(A)
<b>Control Type</b>	Wall mounted controller
<b>Defrost</b>	Auto
<b>Drainage</b>	Continuous drain
<b>Unit Dimensions</b>	49-3" W/ 16x31-1" D / 2x31-78" H
<b>Net Weight</b>	302 LBS.