

# Made in North America

***This seal is to show our commitment to North American standards of manufacturing quality.***



Our products have been tested and continue to be tested to provide consistent performance and value. Our supply of virgin activated carbons is checked upon receipt to make sure that the specifications are met.

Production process is reviewed to maintain the rigorous standards we set for all of the products we make. From the raw materials to the finished goods, we have built a reputation for quality.

## Can 50

**Recommended Exhaust CFM: 420 CFM / 713m<sup>3</sup>h**

@ 0.1 sec contact time

**Pre-filter: Yes**

**Flange: 6" - 8" - 10"**

**Dimensions: (with pre-filter)**

• Outside Diameter: 42 cm / 16.5"

• Height: 50 cm / 19.7"

**Total Weight: 25 kg / 55 lbs.**

**Carbon Weight: 19 kg / 42 lbs.**

**Carbon Bed Depth: 6.5 cm / 2.56"**

**Max Operating Temp: 80°C / 176°F**

**Pressure drop at max CFM: 180pa / .75"wg**

**Recommended Fan:**

	Filtered Air	
FAN	CFM	Watts
10" Max-Fan™	572	212
10" Can-Fan® HO	515	280
8" Max-Fan™	478	152
8" Can-Fan® HO	475	285
8" Can-Fan®	365	134
6" Can-Fan® HO	312	137
6" Max-Fan™	300 (high)	

