

COVERT UFO

MAX AMPERAGE BY VOLTAGE

| VOLTAGE | 100V | 208V | 240V |
|---------|-------|-------|-------|
| 150W | 1.50A | 0.72A | 0.63A |



| | |
|------------------------|---|
| Input Power | 150W |
| Efficacy | 2.1 μmol/s |
| PPF | 315 μmol/s |
| Input Voltage | Autosensing 100-240V |
| Mounting Height | ≥12"(30cm) Above Canopy |
| Thermal Management | Passive |
| Lifetime | 50,000hrs |
| Power Factor | >90% |
| Certifications | UI1598 Damp Location Rating & IP55 (Console Only), CE |
| Colour Rendering Index | 90ra |
| Ambient Temperature | -4~104F |
| Operating Temp Range | -4~185F RH10%-95% |
| Chip | BRANDED LED |
| Fixture Dimensions | 14" H6" (360*H150MM) |
| Fixture Weight | 6.3Lb/2.9kg |


**Please note: Rope Hangers are NOT included

FULL SPECTRUM

Real Full Spectrum (Sunlight) For Plant From Veg Growth TO Bloom. No Need to Change Anything in Whole Growing.



- Array LEDs provide uniform light spread
- Fixture built with high-quality LED Drivers for optimum performance




SILENT OPERATION



High-End & High-Performance
Self-Heating Dissipation Feature.
Loud Fan No Need



Traditional Loud Fan



Other's

PLUG & PLAY



Very convenient and hassle free installation.

- plug & play
- Solid Suspension system
- 1/8 inch adjustable heavy rope hanger

DURABLE HOUSING



Durable aluminum structure is waterproof which ensures long lifespan

HEAT MANAGEMENT



Die-casting aluminum with excellent heat dissipation

LOW ENERGY USE



Energy-efficient LED technology lowers energy usage.