

## VARIUS® LED Series

### 90W Red Spectrum LED Linear Grow Light

#### FEATURES

- Broad spectrum white LED with enhanced red spectral performance ideal for flowering and fruiting cycles
- Each VARIUS® LED bar is supplied with a pre-wired, on-board driver and quick-connect cable system
- Powerful magnets allow the VARIUS® LED to attach directly to pallet rack frames for easy adjustment of bar spacing to customize light intensity and uniformity
- Optional AC supply harness (AG-8-H) for simplified wiring of up to eight bars
- Optional mounting frame (AG-FRAME) offers customizable spacing and spectrum blending, allowing adjustability for any mounting application
- Listed to UL8800

#### SPECIFICATIONS


| Number of Bars                             | Single Bar*   | 8 Bars** |
|--|---|----------|
| PPF (400-700nm) $\mu\text{mol/s}$          | 178   | 1,424    |
| PPF Efficacy (400-700nm) $\mu\text{mol/J}$ | 2.0   |          |
| Lumens                                     | 10,300  | 82,400   |
| CRI  | $\geq 90$   |          |
| Mounting Height                            | 12" to 36"  |          |
| Power Consumption                          | 90W   | 720W     |
| Input Voltage                              | 120-277 VAC   |          |
| Amps @ 120V                                | 0.75A   | 6.0A     |
| Amps @ 240V                                | 0.38A   | 3.0A     |
| Amps @ 277V                                | 0.33A   | 2.7A     |
| Operating Frequency                        | 50/60Hz   |          |
| Operating Temperature                      | $-20^{\circ}\text{C}$ to $40^{\circ}\text{C}$ ( $-4^{\circ}\text{F}$ to $104^{\circ}\text{F}$ ) |          |
| Dimming                                    | 1-10V   |          |
| Environment                                | Damp Location   |          |
| Power Factor (PF)                          | $\geq .98$  |          |
| Certifications                             | ETL / UL8800  |          |

\* Single Bar mounted 18" above canopy.

\*\* Typical Veg Application with eight (8) AG90-R bars spaced 6" apart and mounted 24" above canopy.

#### OTHER SPECTRUMS

- Full-Spectrum - [AG90-W-001](#)
- Blue Spectrum - [AG90-B-001](#)



#### ORDERING INFORMATION


Example: AG90-R-001

| Series/Configuration | Description   |
|----------------------|---|
| AG90-R-001           | LED Light Bar, Red Flower Spectrum, 90W, 120-277VAC Input, 1-10V Dimming, Black Extrusion w/Red End Caps and Driver Connectors, 120VAC Straight Blade Line Cord |


| Accessories *Order as separate line item for final installation in the field |  |
|--|--|
| AG-240-LC  | 240VAC Straight-blade (NEMA 6-15P) Line Cord, 5' Length, for use with AG90 Bars or AC Supply Harness |
| AG-277-L-LC  | 277VAC Twist-lock (NEMA L7-15P) Line Cord, 5' Length, for use with AG90 Bars or AC Supply Harness    |
| AG-8-H   | Multi-port, 16AWG, AC Supply Harness for Linking up to Eight (8) Bars                                |
| AG-FRAME   | 2'x4' Mounting Frame   |

\*Consult factory for additional accessories

ON-BOARD DRIVER



STANDARD MAGNET MOUNT




INCLUDED SAFETY CABLE




ACCESSORIES


2'x4' AG-FRAME



AG-8-H-8 BAR CONNECTOR



AG-240-LC 240VAC CORD W/ PLUG




AG-277-L-LC-277VAC CORD W/ PLUG



RACK DETAIL ILLUSTRATING MAGNET MOUNTING




LIGHT DISTRIBUTION PERFORMANCE



Mounting height varies depending on the application.

DIMENSIONS



WEIGHTS

| Model      | Unit             | Packaged Weight  |
|------------|------------------|------------------|
| AG90-R-001 | 4.8 lbs (2.2kgs) | 5.2 lbs (2.6kgs) |

## VARIUS® LED Series

### 90W Full-Spectrum LED Linear Grow Light

#### FEATURES

- Broad spectrum white LED spectral performance is optimized for all growth cycles
- Each VARIUS® LED bar is supplied with a pre-wired, on-board driver and quick-connect cable system
- Powerful magnets allow the VARIUS® LED to attach directly to pallet rack frames for easy adjustment of bar spacing to customize light intensity and uniformity
- Optional AC supply harness (AG-8-H) for simplified wiring of up to eight bars
- Optional mounting frame (AG-FRAME) offers customizable spacing and spectrum blending, allowing adjustability for any mounting application
- Listed to UL8800

#### SPECIFICATIONS


| Number of Bars                             | Single Bar*   | 8 Bars** |
|--|---|----------|
| PPF (400-700nm) $\mu\text{mol/s}$          | 185   | 1,480    |
| PPF Efficacy (400-700nm) $\mu\text{mol/J}$ | 2.1   |          |
| Lumens                                     | 11,280  | 90,240   |
| CRI  | $\geq 92$   |          |
| Mounting Height                            | 12" to 36"  |          |
| Power Consumption                          | 90W   | 720W     |
| Input Voltage                              | 120-277 VAC   |          |
| Amps @ 120V                                | 0.75A   | 6.0A     |
| Amps @ 240V                                | 0.38A   | 3.0A     |
| Amps @ 277V                                | 0.33A   | 2.7A     |
| Operating Frequency                        | 50/60Hz   |          |
| Operating Temperature                      | $-20^{\circ}\text{C}$ to $40^{\circ}\text{C}$ ( $-4^{\circ}\text{F}$ to $104^{\circ}\text{F}$ ) |          |
| Dimming                                    | 1-10V   |          |
| Environment                                | Damp Location   |          |
| Power Factor (PF)                          | $\geq .98$  |          |
| Certifications                             | ETL / UL8800  |          |

\* Single Bar mounted 18" above canopy.

\*\* Typical Veg Application with eight (8) AG90-W bars spaced 6" apart and mounted 24" above canopy.

#### OTHER SPECTRUMS

- Red Spectrum - [AG90-R-001](#)
- Blue Spectrum - [AG90-B-001](#)



#### ORDERING INFORMATION

Example: AG90-W-001

| Series/Configuration | Description   |
|----------------------|---|
| AG90-W-001           | LED Light Bar, White Full Spectrum, 90W, 120-277VAC Input, 1-10V Dimming, Black Extrusion w/White End Caps and Driver Connectors, 120VAC Straight Blade Line Cord |


| Accessories *Order as separate line item for final installation in the field |  |
|--|--|
| AG-240-LC  | 240VAC Straight-blade (NEMA 6-15P) Line Cord, 5' Length, for use with AG90 Bars or AC Supply Harness |
| AG-277-L-LC  | 277VAC Twist-lock (NEMA L7-15P) Line Cord, 5' Length, for use with AG90 Bars or AC Supply Harness    |
| AG-8-H   | Multi-port, 16AWG, AC Supply Harness for Linking up to Eight (8) Bars                                |
| AG-FRAME   | 2'x4' Mounting Frame   |

\*Consult factory for additional accessories

ON-BOARD DRIVER



STANDARD MAGNET MOUNT




INCLUDED SAFETY CABLE




ACCESSORIES

2'x4' AG-FRAME



AG-8-H-8 BAR CONNECTOR



AG-240-LC 240VAC CORD W/ PLUG




AG-277-L-LC-277VAC CORD W/ PLUG



RACK DETAIL ILLUSTRATING MAGNET MOUNTING




LIGHT DISTRIBUTION PERFORMANCE



Mounting height varies depending on the application.

DIMENSIONS



WEIGHTS

| Model      | Unit             | Packaged Weight  |
|------------|------------------|------------------|
| AG90-W-001 | 4.8 lbs (2.2kgs) | 5.2 lbs (2.6kgs) |

Specifications are subject to change without notice.  
Installation must be performed in accordance with  
Barron Lighting Group installation instructions.



## VARIUS® LED Series

### 90W Blue Spectrum LED Linear Grow Light

#### FEATURES

- Broad spectrum white LED with enhanced blue spectral performance ideal for clone, mother and vegetative cycles
- Each VARIUS® LED bar is supplied with a pre-wired, on-board driver and quick-connect cable system
- Powerful magnets allow the VARIUS® LED to attach directly to pallet rack frames for easy adjustment of bar spacing to customize light intensity and uniformity
- Optional AC supply harness (AG-8-H) for simplified wiring of up to eight bars
- Optional mounting frame (AG-FRAME) offers customizable spacing and spectrum blending, allowing adjustability for any mounting application
- Listed to UL8800

#### SPECIFICATIONS


| Number of Bars                             | Single Bar*   | 8 Bars** |
|--|---|----------|
| PPF (400-700nm) $\mu\text{mol/s}$          | 181   | 1,480    |
| PPF Efficacy (400-700nm) $\mu\text{mol/J}$ | 2.0   |          |
| Lumens                                     | 11,950  | 95,600   |
| CRI  | $\geq 87$   |          |
| Mounting Height                            | 12" to 36"  |          |
| Power Consumption                          | 90W   | 720W     |
| Input Voltage                              | 120-277 VAC   |          |
| Amps @ 120V                                | 0.75A   | 6.0A     |
| Amps @ 240V                                | 0.38A   | 3.0A     |
| Amps @ 277V                                | 0.33A   | 2.7A     |
| Operating Frequency                        | 50/60Hz   |          |
| Operating Temperature                      | $-20^{\circ}\text{C}$ to $40^{\circ}\text{C}$ ( $-4^{\circ}\text{F}$ to $104^{\circ}\text{F}$ ) |          |
| Dimming                                    | 1-10V   |          |
| Environment                                | Damp Location   |          |
| Power Factor (PF)                          | $\geq .98$  |          |
| Certifications                             | ETL / UL8800  |          |

\* Single Bar mounted 18" above canopy.

\*\* Typical Veg Application with eight (8) AG90-B bars spaced 6" apart and mounted 24" above canopy.

#### OTHER SPECTRUMS

- Full-Spectrum - [AG90-W-001](#)
- Red Spectrum - [AG90-R-001](#)



#### ORDERING INFORMATION


Example: AG90-B-001

| Series/Configuration | Description  |
|----------------------|--|
| AG90-B-001           | LED Light Bar, Blue Veg Spectrum, 90W, 120-277VAC Input, 1-10V Dimming, Black Extrusion w/Blue End Caps and Driver Connectors, 120VAC Straight Blade Line Cord |


| Accessories *Order as separate line item for final installation in the field |  |
|--|--|
| AG-240-LC  | 240VAC Straight-blade (NEMA 6-15P) Line Cord, 5' Length, for use with AG90 Bars or AC Supply Harness |
| AG-277-L-LC  | 277VAC Twist-lock (NEMA L7-15P) Line Cord, 5' Length, for use with AG90 Bars or AC Supply Harness    |
| AG-8-H   | Multi-port, 16AWG, AC Supply Harness for Linking up to Eight (8) Bars                                |
| AG-FRAME   | 2'x4' Mounting Frame   |

\*Consult factory for additional accessories

ON-BOARD DRIVER



STANDARD MAGNET MOUNT




INCLUDED SAFETY CABLE




ACCESSORIES


2'x4' AG-FRAME



AG-8-H-8 BAR CONNECTOR



AG-240-LC 240VAC CORD W/ PLUG




AG-277-L-LC-277VAC CORD W/ PLUG



RACK DETAIL ILLUSTRATING MAGNET MOUNTING




LIGHT DISTRIBUTION PERFORMANCE



Mounting height varies depending on the application.

DIMENSIONS



WEIGHTS

| Model      | Unit             | Packaged Weight  |
|------------|------------------|------------------|
| AG90-R-001 | 4.8 lbs (2.2kgs) | 5.2 lbs (2.6kgs) |