

Model:	Date:	
Accessories:		
Accessories.		
Job Name:	Type:	

FULGENT LED

720W 8 BAR LED GROW LIGHT

FEATURES

- Low profile, ideal for indoor cultivation over benches, multi-level vertical racks, and grow tents
- · Foldable design
- · Well balanced full-spectrum
- 0-10V Dimming, 2 RJ ports for smart control (6' RJ cable included)
- 120-277VAC Input, 347-480VAC optional (Please consult factory)
- 120VAC Line cord with plug included (5' length)
- Hanging kit included
- UL Listed, IP65
- Five Year Warranty (Terms and Conditions Apply)


SPECIFICATIONS

Configuration	GLED-FWH-A-VS-FS1
PPF:	1763 μmol/s
Efficacy:	2.48 μmol/J
Light Source:	Samsung / OSRAM
BTUs:	2160 BTU/hrs
Thermal Management:	Passive
Mounting Height above Canopy:	≥ 6"
Coverage Area:	Up to 4' x 4'
Typical Power Consumption:1	720W ± 10%
Input Voltage:	100-277VAC, 347-480VAC Optional
Operating Frequency:	50/60Hz
Operating Temperature:	35°C (95°F)
Dimming: ²	0-10V
Total Harmonic Distortion:	< 15%
Certifications:3	UL, CE, IP65
Warranty:	5 Years

Note:

- ¹ For typical power consumptions please take the GLED-FWH-A-VS-FS1 maximum wattage into consideration when designing facility circuitry (800W). Wattage runs higher at lower input voltages (120VAC) and lower wattages at higher input voltages (277VAC).
- ² Compatible with 0-10V Dimming Controllers (i.e. Trolmaster HCS-1)
- ³ Consult Factory for DLC Qualified Product, optional spectrums and 347-480VAC options. UL Model: MB2-720W27-V1





NOMINAL ELECTRICAL AC INPUT*

AC Voltage	120VAC	208VAC	230VAC	277VAC	347VAC	400VAC	480VAC
AC Current	6.12A	3.64A	3.33A	2.79A	2.23A	1.96A	1.67A
AC Power	720W ± 10%						
Power Factor	0.98	0.95	0.94	0.93	0.93	0.92	0.9

*At 77°F (25°C) ambient temperature.

ORDERING INFORMATION

Example: GLED-FWH-A-VS-FS1


Series/Configuration	Description
GLED-FWH-A-VS-FS1	720W 8 Bar LED Grow Light, Full-spectrum, 120-277VAC, 0-10V Dimming








LIGHT DISTRIBUTION PERFORMANCE



Mounting height varies depending on the application.



DIMENSIONS

Ordering P/N	L	W	Н
GLED-FWH-A-VS-FS1	44.9"	46.5"	2.8"

WEIGHT

Ordering P/N	Packaged Weight	Installed Weight
GLED-FWH-A-VS-FS1	32.5 lbs (14.7 kgs)	26.5 lbs (12 kgs)