The SCC-3 Standard Controller Cabinet is a modular electrical and wire management enclosure system for TrolMaster Control system.

The cabinet is designed to allow the HCS-3 TrolMaster controller to be installed in a clean and professional manner.A pre-cut opening allows TrolMaster's main controller Hydro-X Plus (HCS-3) to be easily installed and provide a proffessional and clean installation for your control system. All device stations can be mounted inside the IP56 rated electrical cabinet to keep the



device stations clean and dry. Users can safely mount and neatly organize the power supplies, modules, and RJ12 cables with ease.

*Note: In order to achieve the IP56 standard, you must use the provided "controller rubber" gasket" and perfectly fit the gasket between the controller and cabinet door.

Specifications

SCC-3

Power Input

Voltage	120V
Max Amps	15A

Working Environments

Ingress Protection	IP56
Temperature	32°F - 104°F / 0°C - 40°C

Cabinet Capacity

Splitter Board Group #1	10 ports (top)
Splitter Board Group #2	6 ports (top)
Splitter Board Group #3	17 ports (top)
Splitter Board Group #4	2 x 4 ports (Detachable Splitter Bars 2 ports (Device) 6 ports (Bottom)
Power Outlet	4+1+6

Cabinet Dimension and Weight Size 6.26" / 159.1mm (L) x 18" / 457.2mm (Ŵ) x 25" / 635mm (H)

Weight 30.49 lbs / 13.83kg

Package Content

Controller Cabinet	1 рс
Controller Rubber Gasket	1 рс
Short RJ-12 Cables	16 pcs
Power Cables (for OA6 modules)	4 pcs
OA6-24 Screw Set	10 pcs
Installation Manual	1 рс


Packaging Dimensions and G.W.

Size	10.43" / 265mm (L) x
	21.65" / 550mm (W) x
	28.35" / 720mm (H)

Power Output

Weight 37.15 lbs / 16.85kg

Mounting Space for HCS-3



TrolMaster

23.43"(595mm)